

ArcGIS Runtime SDK 10.1.1 for Windows Phone

- ESRI.ArcGIS.Client.Toolkit.DataSources Library

ESRI.ArcGIS.Client.Toolkit.DataSources (Namespace)

This screenshot displays the ESRI.ArcGIS.Client.Toolkit.DataSources namespace. It features several class and interface panels:

- AttributionInfo**: Class with Properties: Title.
- CsvLayer**: Class (GraphicsLayer) with Properties: ColumnDelimiter, Credentials, SourceFields, SourceSpatialReference, Url, XFieldName, YFieldName; Methods: Initialize, SetSource; Nested Types: FieldCollection (Class, List<Field>).
- GpsLayer**: Class (GraphicsLayer) with Properties: AccuracyCircleSymbol, AnimateUpdates, GeoCoordinate, GeometryServiceUrl, GeoPositionWatcher, IsEnabled, LocationMarkerSymbol, Position; Methods: Finalize, Initialize, OnMapChanged; Events: GeoCoordinateChanged, PositionChanged.
- KmlLayer**: Class (GroupLayer) with Properties: Credentials, DisableClientCaching, FullExtent, Graphics, Name, ProjectionService, ProxyUrl, RefreshInterval, Url, VisibleLayers; Methods: GenerateVisibilityIds, Initialize, OnMapChanged, QueryLegendInfos, Refresh, SetSource, SetVisibilityByIds.
- OpenStreetMapLayer**: Class (TiledMapServiceLayer) with Properties: AttributionTemplate, Style, TileServers; Methods: GetTileUrl, Initialize; Nested Types: MapStyle (Enum: Mapnik, CycleMap, NoName), TileServerList (Class, List<string>).
- WmmsLayer**: Class (DynamicMapServiceLayer) with Properties: Abstract, AttributionTemplate, ImageFormat, LayerList, Layers, MapUri, ProxyUrl, SkipGetCapabilities, SupportedImageFormats, SupportedSpatialReferenceIds, Title, Url, Version; Methods: GetLayerVisibility, GetUri, Initialize, QueryLegendInfos, SetLayerVisibility; Events: LegendChanged, VisibilityChanged; Nested Types: LayerInfo (Sealed Class, Properties: Abstract, Attribution, ChildLayers, Extent, Name, Title).
- WmtsLayer**: Class (TiledMapServiceLayer) with Properties: Credentials, Description, ImageFormat, Layer, LayerInfos, ProxyUrl, ServiceMode, Style, TileMatrixSet, Title, Token, Url, Version; Methods: GetTileUrl, Initialize; Nested Types: WmtsLayerInfo (Sealed Class, Properties: Abstract, Formats, Identifier, Styles, TileMatrixSets, Title), WmtsServiceM... (Enum: KVP, RESTful).

ESRI.ArcGIS.Client.Toolkit.DataSources.Gps (Namespace)

This screenshot displays the ESRI.ArcGIS.Client.Toolkit.DataSources.Gps namespace:

- GpsSymbol**: Class (MarkerSymbol) with Properties: Course, Size, Speed; Methods: GetAngle, SetAngle.
- VisibleWhenAboveConverter**: Class (IValueConverter) with Methods: Convert, ConvertBack.

ESRI.ArcGIS.Client.Toolkit.DataSources.Kml (Namespace)

This screenshot displays the ESRI.ArcGIS.Client.Toolkit.DataSources.Kml namespace:

- KmlExtendedData**: Class with Properties: DisplayName, Name, Value; Methods: ToString.
- KmlPlaceMarkerSymbol**: Class (MarkerSymbol) with Properties: Fill, Heading, Height, Opacity, Scale, TranslateX, TranslateY, Width.